

HPD 4 Bed Portable Dryers


- 40-60% more energy efficient than wheel dryers with no moving parts!
- Dewpoints as low as -131° F
- Dryers sized to dry all materials not just Polycarbonate
- Faster drying in any ambient conditions
- Ideal for demanding medical resins and applications
- On demand regeneration provides stable temperatures at the drying hopper



HP's stacked tower design provides faster drying and no moving components for trouble free, reliable operation

Dri-Air vs. Wheel

Energy Comparison @ 50 lbs/hr
Cost Per Year @ 10¢ per kw/hr



DRI-AIR
Industries, Inc.

www.dri-air.com

Call us at 860.627.5110

HPD Series

More efficient, more air flow and lower dewpoints equal faster, more energy efficient drying than wheel and compressed air dryers. Dri-Air HPD dryers include our patented 4 bed dryer, drying hopper and optional closed loop loading systems, eliminating press/extruder mounted drying hoppers, for fast, safe material changes.



HPD-13

Integrated Hopper Loader

Available with PD dryers having our closed loop loading system. Brushless hopper loading eliminates noisy, maintenance-prone vacuum motors.

- One power connection
- Completely self-contained
- Available with single or proportioning (virgin/regrind) hopper loaders



HPD with integrated hopper loader

Portable Dryers – Controls & Closed Loop Loader

Dri-Shot Loader

Convey dried material with dry-air, eliminating moisture contamination with compressed or ambient plant air. Closed loop loaders are available with portable dryers or as stand-alone units. Eliminate press/extruder mounted drying hoppers.



DS-2 receiver

DS-1 receiver

- Stainless steel construction with internal flap valve that provides a positive seal at the throat – simplifies installation on color feeders, slide gates, swing arms or magnet drawers

- SmartTouch Controller can communicate with SmartView interface for monitoring your dryers on your desktop

| HPD Model | Process Rate | | Hopper Capacity | | Dimensions | |
|-----------|--------------|---------|-----------------|------|--------------|-------------|
| | (lbs/hr) | (kg/hr) | (lbs) | (kg) | [l/w/h] inch | [l/w/h] cm |
| 1 | 10 | 5 | 30 | 14 | 25/39/57 | 64/99/145 |
| 2 | 20 | 10 | 60 | 27 | 25/39/62 | 64/99/169 |
| 3 | 30 | 14 | 100 | 45 | 25/39/60 | 64/99/152 |
| 4 | 40 | 18 | 150 | 68 | 25/39/73 | 64/99/185 |
| 5 | 50 | 25 | 150 | 68 | 30/52/75 | 76/152/191 |
| 6 | 60 | 27 | 200 | 91 | 30/52/69 | 76/152/175 |
| 7 | 80 | 36 | 300 | 136 | 30/52/84 | 76/152/213 |
| 8 | 100 | 45 | 300 | 136 | 30/52/84 | 76/152/213 |
| 9 | 125 | 50 | 400 | 181 | 50/42/92 | 127/107/234 |
| 10 | 160 | 73 | 600 | 272 | 50/42/112 | 127/107/284 |
| 11 | 220 | 100 | 600 | 272 | 50/42/112 | 127/107/284 |
| 13 | 300 | 150 | 1000 | 453 | 66/42/116 | 167/107/295 |



SMART TOUCH Controls

- Our new SmartTouch Control is standard on our HPDII dryers and is Industry 4.0 ready! OPC/UA open communication through the optional Ethernet switch or WIFI Bridge for wireless communication. Other features include 7" HMI, -49°F dewpoint monitor, 7 day timer, resin library, dewpoint and temperature trending, alarms, diagnostics, event log, run and filter timers, 3 level password protection and optional temperature setback to prevent overdrying!

SMARTVIEW Interface

- Our new SmartView desktop app lets you see the big picture – multiple dryers on your desktop without walking the plant floor. Connect through our available Ethernet switch or wirelessly with our available WIFI bridge for a cable free installation. View and set temperatures and alarms all from one location.



www.dri-air.com

Call us at 860.627.5110